Imperial College London

Help – I Need Somebody! Deferring to Humans for Sequential Decision-Making in Uncertainty

Sonali Parbhoo, PhD.

Assistant Professor of Machine Learning

AI for Actionable Impact (AI4AI) Lab

Department of Electrical and Electronic Engineering

Imperial College London

26 October 2022

Machine Learning is changing the way we make decisions



ML is also very successful in *some domains*



The Beatles



Not The Beatles



Prime Minister




Not the Prime Minister

Human beings are natural experts in these domains

Image Credits:
https://www.wikipedia.org
https://www.news.sky.com

But machine learning has had less success in *high-risk settings*



Why?

High stake decision-making is challenging *even for humans*



What treatment should a patient take?



How should a teacher assist a student?




Should a suspect be convicted?


Why?

High stake decision-making is challenging *even for humans*



What treatment should a patient take?





There is no one size fits all

[1]Smith, Saunders et al. Best Care at Lower Cost: The Path to Continuously Learning Healthcare in America, 2013.

Decisions often have *long-term* consequences





Image credit: David Sontag – ML for Healthcare, 6.871

Reinforcement Learning for Long-Term Decision-Making


Medicine is inherently a sequential decision making problem:

- Clinicians, with their best understanding of a patient's status, propose a treatment.
- Patient status may change as a result of the treatment.
- Outcomes are a result of prior treatments.

RL makes this process explicit




Example: HIV Therapy Management




- Requires life-long treatment with *combinations of antiretrovirals*.
- Virus is highly mutagenic and can become drug resistant.
- Patients exhibit significant heterogeneity.

Example: HIV Therapy Management

- Treatments consist of five classes of drugs: NNRTIs, NRTIs, PIs, IIs, FIs
- The virus mutates in response to treatments leading to *drug resistance*



Solution: Train a model over *long-term outcomes*



Modelling HIV as an RL problem can help determine treatments that may work in the long-term (e.g. Ernst 2007; Parbhoo 2014; Marivate 2015), *but often in simplified/simulation settings only.*

The expected return (value) at the current state *s* is:

The expected reward for taking action *a* at state *s*...

$$V(s) = \max_a (R(s,a) + \gamma V(s'))$$

The maximum value of any possible action *a* for:

...plus the discount factor (gamma) multiplied by the value of the next state


Modeling Long-Term Consequences is Helpful

- Cohort: 32960 patients from EuResist Database
- Observations: CD4s, VLs, mutations, clinical variables
- Actions: 312 most frequently occurring drug combinations (from 25 drugs)

Baseline	Value
Random Policy	-7.31 +/- 3.72
Neighbour Policy	6.35 +/- 2.61
Long-term Policy	**11.52 +/- 1.31**

Combining Kernel and Model-based RL for HIV Therapy Selection –Parbhoo et al 2016, AMIA


…. But Evaluation Can Be Brittle



Baseline	Value
Random Policy	-7.31 +/- 3.72
Neighbour Policy	6.35 +/- 2.61
Long-term Policy	11.52 +/- 1.31
Long-term Policy on SA data	**4.26 +/-2.17**

Evaluating Reinforcement Learning Algorithms in Observational Health Settings– Gottesman et al 2017, Nature Medicine

…. But Evaluation Can Be Brittle




Baseline	Value
This occurs because of the spread of the treatments administered	
SA data	

Evaluating Reinforcement Learning Algorithms in Observational Health Settings– Gottesman et al 2017, Nature Medicine

Uncertainty *matters*

	Gender	Glucose	AST	Age
Patient 1	?	120	?	?
Patient 2	M	105	?	68
Patient 3	F	203	45	63
Patient 4	M	145	?	42
Patient 5	M	89	?	80

Data:
Missingness in EHR records



Diagnosis:
ARDS or pneumonia?



Diagnosis:
In-distribution or outlier?



Treatment:
Drug A or Drug B?


Though we cannot always eliminate these, knowledge about such uncertainties can help us learn *how to act*.

Why is uncertainty important?

All models are wrong, but models that know when they are wrong, are useful.

– Dustin Tran, 2020

- Generalisation and transfer learning
- *Safety*
- Active Learning
- *Reducing overreliance and trust*
- Fairness
- Interpretability
- Causality




Don’t apply model to patients outside study group

Uncertainty estimation: Bayesian Methods

- Bayesian methods represent uncertainty using a *distribution over parameters:*

$$\overbrace{p(\theta|\mathbf{X})}^{\text{Posterior}} \propto \underbrace{p(\mathbf{X}|\theta)}_{\text{Likelihood}} \overbrace{\pi(\theta)}^{\text{Prior}}$$



Uncertainty estimation: Bayesian Methods

Model: A probabilistic model is a joint distribution of outputs **y** and parameters $\boldsymbol{\theta}$ given inputs **x**.

$$p(\mathbf{y}, \boldsymbol{\theta} \mid \mathbf{x})$$


Training time: Calculate the **posterior**, the conditional distribution of parameters given observations.

$$p(\boldsymbol{\theta} \mid \mathbf{x}, \mathbf{y}) = \frac{p(\mathbf{y}, \boldsymbol{\theta} \mid \mathbf{x})}{p(\mathbf{y} \mid \mathbf{x})} = \frac{p(\mathbf{y} \mid \mathbf{x}) p(\boldsymbol{\theta})}{\int p(\mathbf{y}, \boldsymbol{\theta} \mid \mathbf{x}) \, \mathrm{d}\boldsymbol{\theta}}$$

Prediction time: Compute the likelihood given parameters, each parameter configuration of which is weighted by the posterior.

$$p(\mathbf{y} \mid \mathbf{x}, \mathcal{D}) = \int p(\mathbf{y} \mid \mathbf{x}, \boldsymbol{\theta}) p(\boldsymbol{\theta} \mid \mathcal{D}) \, \mathrm{d}\boldsymbol{\theta} \approx \frac{1}{S} \sum_{s=1}^{S} p(\mathbf{y} \mid \mathbf{x}, \boldsymbol{\theta}^{(s)})$$

Epistemic Uncertainty



Many models with varying parameters may fit the training data well.


- Uncertainty about the choice of model that generated our data is known as *epistemic uncertainty*.
- Model uncertainty is *reducible*:
  - it decreases with more data (subject to model identifiability)

Aleatoric Uncertainty

- Uncertainty about the data is known as *aleatoric uncertainty*.

- Data uncertainty is *irreducible**:
  - Persists even under infinite data
  - **Can be reduced by using additional features/views*

- Labelling noise (e.g. human disagreement)
- Measurement error (e.g. imprecise devices)
- Missing data (e.g. partially observed features *or hidden confounders*)



Diabetic retinopathy detection from fundus images - Gulshan et al, 2016

Applying Bayesian Methods in Practice


- Using Bayesian models to make inferences can help us reason about uncertainties in different scenarios.

- If such a model makes inaccurate predictions and has high epistemic uncertainty, one may *prefer to use another model* to make predictions.


- However, if a model makes reasonable predictions, but has high aleatoric uncertainty, *one needs to be very careful who the model is applied to as it may be unsafe beyond the data distribution.*

Learning to Defer to Humans in Uncertainty

- Human expertise is valuable in high-risk settings such as healthcare.
- Domain experts can often *provide additional knowledge* that can help reduce uncertainties for rare cases or outlier patients.
- Though prior works have explored ways to combine humans and models, none of these account for *uncertainty and long-term effects.*




Combining Kernel and Model-based RL for HIV Therapy Selection – Parbhoo et al, 2017, AMIA




Consistent Estimators for Learning to Defer to an Expert – Mozannar et al, 2020, ICML

Help - I need somebody! Deferring to Humans in Uncertainty




Help - I need somebody! Deferring to Humans in Uncertainty



Help - I need somebody! Deferring to Humans in Uncertainty

Quantify where a *model cannot be trusted*

Model *changing dynamics* and *uncertainty*




Quantify impact of *delaying deferral*

Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Help - I need somebody! Deferring to Humans in Uncertainty

Quantify where a *model cannot be trusted*




Model *changing dynamics* and *uncertainty*

Quantify impact of *delaying deferral*

Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.


Help - I need somebody! Deferring to Humans in Uncertainty



Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Modeling Changing Dynamics


Step 1: Learn a model of *non-stationary* dynamics $\{\mathcal{M}_t\}_t$




Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Modeling Changing Dynamics

Step 1: Learn a model of *non-stationary* dynamics $\{\mathcal{M}_t\}_t$



Step 2: Use posterior sampling to capture *uncertainty over models* $\mathcal{M}_t \sim p(\cdot|\mathcal{D})$



Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Sequential Learning to Defer (SLTD)

Step 3: Quantify the impact of *delaying deferral*

$$\mathbb{E}_{\mathcal{M}\sim p_t(\cdot|\mathcal{D})}\left[\mathbf{1}(V^{\mathcal{M}_k}_{\pi_{\mathrm{tar}(t),\mathrm{mix}(t_+)}} < V^{\mathcal{M}_k}_{\pi_{0(t),\mathrm{mix}(t_+)}} - c)\right]$$

Defer later

Defer now

Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Sequential Learning to Defer: Algorithm

Algorithm 1 Sequential Learning to Defer

Input: $\mathcal{D}^*$, behavior policy π_0, target policy π_{tar}.
Estimate Posterior Distributions $\{\mathcal{M}_t \triangleq p_t(\cdot|\mathcal{D}^*)\}_{t=0}^{T}$ (posteriors over rewards not shown here)
Initialization: Deferral function $g_{\pi_{\text{tar}}}(s,t) = 0$ for all $s \in \mathcal{S}$ and $t \in \{1, 2, \cdots, T\}$.
for $n \in$ BOOTSTRAPS($\mathcal{D}^*$) **do**
  Sample $\boldsymbol{\mathcal{M}}_k \triangleq \{\mathcal{M}_{k,t} \sim p_t(|\mathcal{D}*)\} \forall t \in \{1, 2, \cdots, T\}, \forall k \in \{1, 2, \cdots, K\}$
  for $t \in \{T, T-1, \cdots, 1\}$ **do**
    for $s \in \mathcal{S}$ **do**
      Compute $V^{\boldsymbol{\mathcal{M}}}_{\pi_{\text{tar}(t),\text{mix}(t_+)}}$, $V^{\boldsymbol{\mathcal{M}}}_{\pi_{0(t),\text{mix}(t_+)}} - c \forall \boldsymbol{\mathcal{M}}$
      $\tilde{g}_{\pi_{\text{tar}}}(s,t) \leftarrow\approx \frac{1}{K} \sum_{\boldsymbol{\mathcal{M}}_k \sim \{p_t(\cdot|\mathcal{D})\}_t} [\mathbf{1}(V^{\boldsymbol{\mathcal{M}}_k}_{\pi_{\text{tar}(t),\text{mix}(t_+)}} < V^{\boldsymbol{\mathcal{M}}_k}_{\pi_{0(t),\text{mix}(t_+)}} - c)]$
    end for
  end for
end for
return $g_{\pi_{\text{tar}}}(s,t) = \mathbf{1}(\tilde{g}_{\pi_{\text{tar}}}(s,t) > \tau) \forall s, t \in \mathcal{S} \times \{1, 2, \cdots, T\}$

Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Decomposing the uncertainty at deferral

- The outcome we are interested in is

$$\mathbb{E}[r_T|s_{t_d},\mu_{t_d}] = \int_{s_{t_d+1}}^{s_T}\int_{a_{t_d}}^{a_T}\int_{\mu_{t_d+1}}^{\mu_T}\int_{\theta_{t_d}}^{T} r(s_T,a_T)\prod_{t'=t_d+1}^{T} p(s_{t'}|\mu_{t'})p(\mu_{t'}|\theta'_t(s_{t'},a_{t'}))\pi_{t'}(a_{t'}|s_{t'})p(\theta_{t'}|\mathcal{D})d\mathbf{s}_{t_d+1}^{T}d\mathbf{a}_{t_d}^{T}d\boldsymbol{\mu}_{t_d+1}^{T}d\boldsymbol{\theta}_{t_d}^{T}$$

Decompose

$$\underbrace{\mathrm{Var}(r_T|s_{t_d},\mathcal{D})}_{\text{Total Uncertainty}} = \underbrace{\mathbb{E}_{\mu_{t_d}\sim p(\mu_{t_d}|\mathcal{D})}[\mathrm{Var}(r_T|\mu_{t_d},s_{t_d},\mathcal{D})]}_{\text{Irreducible/ Aleatoric Uncertainty}} + \underbrace{\mathrm{Var}_{\mu_{t_d}\sim p(\mu_{t_d}|\mathcal{D})}(\mathbb{E}[r_T|\mu_{t_d},s_{t_d},\mathcal{D}])}_{\text{Epistemic/Modeling Uncertainty}}$$

- First term averages over the variance due to μ_{t_d} and captures **aleatoric uncertainty** at t_d
- Second term captures variance conditioned on knowledge of the model or **epistemic uncertainty** at deferral time.

Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

What can these uncertainties tell us?

- **High Epistemic Uncertainty:**
  - Uncertainty of model's prediction is high
  - Possible improvement if additional data in this region could be collected to improve the reducible sources of uncertainty.

- **High Aleatoric Uncertainty:**
  - There is high variability in the patient's dynamics that may need to be managed with careful interventions or is otherwise not manageable.
  - Aleatoric uncertainty is *important for safety*

- Based on uncertainty, expert may choose to deviate from practice and/or get second opinions.


Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Toy Demonstration

- Given 8 states: s6 has reward -5; while others have reward +1
- Each sample starts at s0 and progresses to s7
- Two actions: a0 decreases chances of landing in s6; a1 increases this
- Target policy π_{tar} increases the chances of landing in s6 from {s2, s3, s4} at times 3-8.
- Non-stationarity increases over time, while rewards are positive in {s2, s3, s4} so that poor outcomes only manifest in the future.
- A pre-emptive deferral policy should defer between times 3 and 8.

Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Optimizing for long-term outcomes learns *qualitatively different deferral policies*




Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

SLTD's policy improves *long-term outcomes*

Method	Synthetic		Diabetes		HIV - Case Study I	
	Value (mean ± 2 s.e.)	Defer Frequency	Value (mean ± 2 s.e.)	Defer Frequency	Value (mean ± 2 s.e.)	Defer Frequency
SLTD	**8.029 ± 0.039**	0.509	**36.931 ± 0.166**	0.396	**14.792 ± 0.267**	0.342
SLTD-Stat.	5.588 ± 0.048	1.000	34.326 ± 0.172	1.000	11.020 ± 0.230	0.629
SLTD-One Step	5.578 ± 0.050	1.000	36.819 ± 0.23	0.412	9.671 ± 0.129	0.531
SLTD (K=1)	8.011 ± 0.025	0.511	36.678 ± 0.289	0.297	9.311 ± 0.162	0.517
SLTD-Stat. (K=1)	5.575 ± 0.036	1.000	34.320 ± 0.175	1.000	8.659 ± 0.027	0.571
SLTD-One Step (K=1)	5.595 ± 0.038	1.000	36.482 ± 0.284	0.328	8.640 ± 0.104	0.318
Augmented-MDP	3.044 ± 0.023	0.512	13.273 ± 0.126	0.000	N/A	N/A
Mozannar et. al.	6.369 ± 2.226	0.468	-15.155 ± 0.675	0.010	3.820 ± 0.231	0.291
Madras et. al.	5.731 ± 0.223	1.000	35.388 ± 0.475	0.332	3.330 ± 0.481	0.400
π_{tar}	-1.80 ± 0.071	N/A	13.202 ± 0.162	N/A	5.837 ± 0.171	N/A
π_0	5.485 ± 0.035	N/A	34.241 ± 0.151	N/A	14.124 ± 0.592	N/A


Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

SLTD produces better outcomes with *fewer deferrals*




Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.


Deferring early potentially *reduces overall uncertainty*



SLTD



Stationary



One-step

Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Decomposing the uncertainty can help us interpret *why we need to defer*


	Defer Time t_d	Total Uncertainty	Modeling Uncertainty	Mean Outcome
Synthetic data	3	26.190	0.233	3.42
Diabetes	3	3418.17	34.160	73.669

Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Summary

- High stake decisions have **long-term consequences** and are often applied in exceptional situations where generalisation is hard
- Our work provides a means of **quantifying risk** in sequential settings, such that one may **defer to a domain expert where necessary.**
- Based on the uncertainty, one may also learn **when to collect more data or retrain the model.**
- Future work may explore how this uncertainty can be incorporated into an active learning setting to improve model performance or identify areas such as dead-ends.

Help – I need somebody… Not just anybody!



Pre-emptive learning to defer for sequential decision-making in uncertainty –Parbhoo*, Joshi* and Doshi-Velez 2022, arXiv preprint.

Summary

- High stake decisions have **long-term consequences** and are often applied in exceptional situations where generalisation is hard
- Our work provides a means of **quantifying risk** in sequential settings, such that one may **defer to a domain expert where necessary.**
- Based on the uncertainty, one may also learn **when to collect more data or retrain the model.**
- Future work may explore how this uncertainty can be incorporated into an active learning setting to improve model performance or identify areas such as dead-ends.